

**DECLARATION OF PERFORMANCE****No 3P-B1F-A-003**

According to regulation No 305/2011

|   |  |
|---|--|
| Unique identification code of the product-type: | <b>Factory made expanded polystyrene (EPS) products</b><br>EPS EN 13163 T1 -L2-W2 -S1 -P5 -BS 170 -CS(10)120-<br>DS(N)2-DS(70,-)1-WL(T)3,5   |
| Product name:                                   | <b>TENAPORS SUPRA EPS 120, thickness from 30 mm to 200 mm</b>  |
| Intended use:                                   | <b>For thermal insulation of buildings</b>   |
| Manufacturer:                                   | <b>TENAPORS, Ltd.,</b><br>Spodriības 1, Dobele, Latvia, LV- 3701<br>Tel.+371 63720901, fax +371 63724371<br>e-mail: tenapors@tenaxgrupa.lv   |
| System/s of AVCP                                | Scheme 3 (thermal conductivity /thermal resistance, compressive stress, reaction to fire)<br>Scheme 4  |
| Harmonised standard:                            | EN 13163:2012+A1:2015  |
| Notified body/ies:                              | No 1688 - Vilniaus Gedimino Technikos Universitetas,<br>Termoizoliacijos Mokslo Institutas (Linkmenu 28, 08217 Vilnius,<br>Lithuania)<br><br>No 2040- Limited liability company "Forest and Wood Products<br>Research and Development Institute" Testing laboratory (Dobeles<br>41, Jelgava, Latvia) |

The performance of the product identified above is in conformity with the set of declared performance/s (see attachment No 1). This declaration of performance s issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:  
TENAPORS, Ltd. Head of the Laboratory

.....  
Iveta Audzēviča  
14.08.2017.

### Attachment No 1 to Declaration of Performance 3P- B1F-A-003

Factory made expanded polystyrene(EPS) products TENAPORS SUPRA EPS 120 , thickness from 30 mm to 200 mm

| Year when CE mark was affixed  |                          | 14 -plant -Aleja 12a, Valmiermuiža,<br>Valmiera parish.,Burtnieki municipality |             |      |
|--|--------------------------|--|-------------|------|
| Essential characteristics <sup>1)</sup>  | Units, classes or levels | Testing standard   | Performance |      |
| Thermal conductivity coefficient, W/(m·K)(all thickness)   | W/m×K                    | EN 12667<br>EN 12939   | 0,036       |      |
| Thermal resistance at specified thickness  | m <sup>2</sup> ×K/W      | EN 13163   | 30 mm       | 0,80 |
|  |                          |  | 40 mm       | 1,10 |
|  |                          |  | 50 mm       | 1,35 |
|  |                          |  | 60 mm       | 1,65 |
|  |                          |  | 70 mm       | 1,90 |
|  |                          |  | 80 mm       | 2,20 |
|  |                          |  | 90 mm       | 2,50 |
|  |                          |  | 100 mm      | 2,75 |
|  |                          |  | 120 mm      | 3,30 |
|  |                          |  | 150 mm      | 4,15 |
| 200 mm   | 5,55                     |  |             |      |
| Reaction to fire of the product as placed on the market  | class                    | EN 13501-1   | E           |      |
| Water absorption   | %                        | EN 12087   | WL(T)3,5    |      |
| Thickness tolerance  | class                    | EN 823   | T1          |      |
| Width tolerance  | class                    | EN 822   | W2          |      |
| Length tolerance   | class                    | EN 822   | L2          |      |
| Squareness tolerance   | class                    | EN 824   | S1          |      |
| Flatness tolerance   | class                    | EN 825   | P5          |      |
| Compressive stress at 10 % deformation   | level                    | EN 826   | CS(10)120   |      |
| Bending strength   | level                    | EN 12809   | BS 170      |      |
| Tensile strength   | level                    | EN 1607  | NPD         |      |
| Dimensional stability under constant normal laboratory conditions  | level                    | EN 1603  | DS(N)2      |      |
| Dimensional stability at specified temperature   | level                    | EN 1604  | DS(70,-)1   |      |
| NOTE   |                          |  |             |      |
| 1) All other essential characteristics are not declared and are classified as <i>NPD (No Performance Determined)</i> |                          |  |             |      |